Table of Contents

SMTP 3
Todo 3
Email //to// the new tux is received and handled 3
Tested by: 3

TuxSoftware

SMTP

Todo

- clear out test mail

Email //to// the new tux is received and handled

Tested by:

```
add to my own /etc/hosts:
74.104.50.63 newtux tux
```

```
ssh -x -p 28 -L2525:tux:25 tux
```

```
From my machine:

bjb@charmeleon ~ 507 $ nc localhost 2525
220 tux.oclug.on.ca ESMTP Postfix (Debian/GNU)
EHLO stuffed.animals
250-tux.oclug.on.ca
250-PIPELINING
250-SIZE 10240000
250-VRFY
250-ETRN
250 8BITMIME
MAIL FROM:  bjb@stuffed.animals
250 Ok
RCPT TO:  bbutler@oclug.on.ca
250 Ok
DATA
354 End data with <CR><LF>.<CR><LF>
ehlo stuffed.animals
mail from:  bjb@stuffed.animals
rcpt to:  bbutler@oclug.on.ca

.
250 Ok: queued as 6B42D1029C7
421 tux.oclug.on.ca Error: timeout exceeded
```

```
bjb@charmeleon ~ 508 $
```

- the email shows up in bbutler's mail /var/mail/bbutler
- email to bjb@newtux is rejected (newtux is not known as a local hostname) (this is good)

From:
https://wiki.linux-ottawa.org/ - **Linux-Ottawa (OCLUG) Wiki**

Permanent link:
https://wiki.linux-ottawa.org/doku.php?id=hwmig2007smtp

Last update: **2015/06/09 19:23**