

Table of Contents

The Trac Configuration File	3
<i>Global Configuration</i>	3
<i>Reference</i>	3
<i>[[:components]]</i>	3

The Trac Configuration File

[\[TracGuideToc\]](#)

Trac configuration is done by editing the `trac.ini` config file, located in `<projectenv>/conf/trac.ini`.

Global Configuration

Since version 0.9, Trac can also read the configuration from a global `trac.ini` file. These global options will then be merged with the environment-specific options, where local options override global options.

The global configuration is by default located in `$prefix/share/trac/conf/trac.ini`. It can be moved to a different location (for example, `/etc/trac.ini`), but that requires changing the file `trac/siteconfig.py` which gets created when Trac is installed.

Reference

This is a brief reference of available configuration options.

[\[TracIni\]](#)

[[:components]]

(since 0.9)

This section is used to enable or disable components provided by plugins, as well as by Trac itself. The component to enable/disable is specified via the name of the option. Whether its enabled is determined by the option value; setting the value to `enabled` or `on` will enable the component, any other value (typically `disabled` or `off`) will disable the component.

The option name is either the fully qualified name of the components or the module/package prefix of the component. The former enables/disables a specific component, while the latter enables/disables any component in the specified package/module.

Consider the following configuration snippet:

```
[[:components]]
trac.ticket.report.ReportModule = disabled
webadmin.* = enabled
```

The first option tells Trac to disable the [report module](#). The second option instructs Trac to enable all

components in the `webadmin` package. Note that the trailing wildcard is required for module/package matching.

See the *Plugins* page on *About Trac* to get the list of active components (requires `CONFIG_VIEW` [permissions](#).)

See also: TracPlugins

```
//Note that prior to Trac r2335 (that applies to 0.9b1 and 0.9b2), you would use a `[[[:disabled_components]]` section instead. See a [[http://projects.edgewall.com/trac/wiki/TracIni?version=42|previous version]] of this page for the details.//
```

See also: TracGuide, TracAdmin, TracEnvironment

From:

<https://wiki.linux-ottawa.org/> - **Linux-Ottawa (OCLUG) Wiki**

Permanent link:

<https://wiki.linux-ottawa.org/doku.php?id=tracini>

Last update: **2015/06/09 19:23**

